
## Antirutschmatte Cushion Dek (TM) Grip Step







- Aggressive slip resistant surfaces with abrasive anti-slip coating.
- Slot perforations (13 mm x 48 mm) facilitate drainage of fluids, keeping the surface clean.
- Designed to withstand harsh chemicals, this mat offers simple solutions to almost any industrial or foodservice application.
- Made of tough PVC compound, designed to yield a long service life and resist to industrial oils.
- Easy roll-up and clean-up.
- Free of silicone therefore safe for vehicle painting facilities.
- Ergonomic benefit of 11 mm thickness worker platform
- Top surface with raised pyramid configuration enhances traction while channeling liquids.
- Free of toxic DOP and DMF.

	PF	RODUCT SPECIFICATIONS	
Designation	Industrial Matting		
Туре	Anti-slip		
Description	Duckboard, pyramid configured top surface with slotted perforations, resistant to industrial oil		
Material	100% PVC		
Process	Injection moulding		
Category	Good		
Recommended use	Medium duty – industrial environments, wet/dry areas – extremely slippery areas		
Colours	Black		
Weight	6.5 kg/m <sup>2</sup>		
Thickness	11 mm		
Standard sizes	91 cm x 122 cm 91 cm x 182 cm 91 cm x 300 cm 91 cm x 10 m		
Custom sizes	60 cm, 91 cm, 122 cm, 182 cm per linear meter		
Special remarks	With Grip Step® abrasive anti-slip coating		
9/// ///		PRODUCT TESTING	
	Tests	Norms	Results
Compression deflection		U.S.	
	1.4 kg/cm <sup>2</sup>		1.82 cm
	2.8 kg/cm <sup>2</sup>		1.66 cm
Foam battery		ASTM D3574	
Abrasion resistance		ASTM D3884-01	
	500 Cycles		
	5000 Cycles		0.57
Static coefficient of friction		ASTM C1028-96	
Elongation		ASTM D412	
Breaking load		ASTM D412	
Graves tear strength		ASTM D 1004	
Hardness		ASTM D2240-02	
Anti-slip		DIN 51130 and BG-RULE BGR181	1
		FIRE TESTING	
	Critical radiant flux	ASTM E-648	
	Fire retardancy	DIN4102	
		EN 13501-1	
	Flammability test	ASTM D2859	
ESD		ANSI ESD S7.1 50% Humidity	
Sustainability		<ul> <li>Recyclable material</li> <li>Reach Compliant (Registration, Evaluation, Authorization an Restriction of Chemicals)</li> </ul>	

## Zu beziehen bei:

www.arbeitsplatzmatten-profi.com, info@arbeitsplatzmatten-profi.com, Tel. 0049 63 59 96 11 906